



# GT-13

## Medium Duty Mulcher



### LEAN GREEN MULCHING MACHINES

If rougher, steeper terrain dominates your region, but you need the benefits of a compact, lightweight highly-maneuverable machine, then look to Gyro-Trac's light- to medium-duty GT-13. Its captive track system allows for more aggressive use on inclines, and its powerful 125-horsepower turbo diesel engine can tackle more trees in less time. Coupled with Gyro-Trac's new planar-head technology, the GT-13 outperforms any other machine in its class by more than 2 to 1.



# GT-13

## Medium Duty Mulcher



## Standard Specifications

### DIMENSIONS

Track Width	19"	482.60 mm
Overall Length	203"	5156.2 mm
Overall Width	74"	1879.60 mm
Overall Height	104"	2641.6 mm
Weight	13,540 lbs.	6154.5 kg
Ground Clearance	13"	330.2 mm
Ground Pressure	3.5 Psi	

### ENGINE

Cummins Turbo Diesel (QSB 3.9 TAA)

No. of Cylinders	4	
HP @ 2200 RPM	125 HP	
Torque @ 1500 RPM	355 lb-ft.	481.38 N.m

### CAPACITIES

Fuel Tank	44.6 US Gal.	37.14 Imp. Gal.	168.78 L
Hydraulic Tank	21.3 US Gal.	17.74 Imp. Gal.	80.61 L

All specifications subject to change without notice.

### STANDARD FEATURES

- Low-profile fully-enclosed tilt cab
- Comfortable suspension seat
- Exceeds SAE ROPS/FOPS specifications
- 6 halogen lights
- Auxiliary hydraulic
- Lexan safety windshield
- Rear sweeps for cab and systems protection
- 12,000 lb. winch
- Pressurized cabin to keep out dust and smoke

### HYDRAULICS

- Closed-system Sundstrand Series 90 pumps and Rexroth motors
- Sundstrand's Plus 1™ digital monitoring and control system optimizes performance while it protects equipment from damage

### STEERING

- Hydrostatic drive/steer system with single joystick control

### TRACKS

- Six (6) nylon and polyester reinforced rubber tracks, assembled with heat-treated steel crosslinks
- Patented Captive-Track system makes throwing a track nearly impossible
- Optional rubber "soft-track" for even more environmentally and mechanically sensitive operation

### CUTTER HEAD

- Exclusive patented spiral-tooth mounting design
- Bosch/Rexroth hydraulic work head power supply
- Individually-mounted teeth replace in just minutes
- Drum speed: 2200 RPM
- Optional swing-tooth flail drum for rockier terrain – designed to bounce off hard surfaces and fall back into a pocket to lengthen tooth life



*"... I've been in the mulching business for over 30 years, and the planar head is the most significant advancement I've ever seen ... it blows everything else away ..."*

—John O'Hagan, Rowmec

