

GT-18 STANDARD SPECIFICATIONS



DIMENSIONS

Track Width	28"	711mm
Overall Length	232"	5886mm
Overall Width	108"	2743mm
Overall Height	109"	2768mm
Weight	19 000lbs	8616kg
Ground Clearance	14"	356mm
Ground Pressure	2.0 PSI	13.78 kPa

ENGINE

Cummins Turbo Diesel	6 BTA	
Number of Cylinders	6	
HP @ 2000 RPM	199 HP	
Torque @ 1650 RPM	446 lb/ft	595 N.m

CAPACITIES

Fuel Tank	60 US Gallons	227 ltr
Hydraulic Res	38 US Gallons	144 ltr

FRAME

Watertight tub made of highly resistant heat-treated steel.

STEERING

System matched single joystick for forward, reverse, left, right and speed.

TRACKS

Six ply nylon and polyester reinforced rubber tracks, assembled with heat-treated steel crosslink's.

Captive track system: With our patented system it is impossible to through a track, no mater what terrain you are in.

CUTTER HEAD



Toma-Ax 700 H with patented spiral tooth mounting design

Individually replaceable teeth

Drum Speed: 2200 RPM

STANDARD FEATURES

- Low profile fully enclosed tilt cab
- Suspension seat
- Wire mesh
- 6 halogen lights (2 front-2 Side-2 Rear)
- Auxiliary hydraulics
- Swing-Out radiator
- Lexan windshield
- Rear Sweeps for cab and systems protection
- Rear Bumper (T1 Steel) – weight adjustable for optimum machine performance
- 12,000 lbs winch
- Pressurized cabin to keep out dust and smoke